QSAND Sanq Power

Model : SQC565-6 (S)

Standby Power (60Hz)	565KVA/450KW
Prime Power(60Hz)	513KVA/410KW

Standard Features

- Engine: Cummins KTA19-G3
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford HCI444F
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)
Open type	3350mmx1280mmx1934mm	3850
Silent type	4800mmx1683mmx2200mm	6520

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	60	3	0.8	565/450	513/410

Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







QSAND Sanq Power

Engine Data

5	
Manufacturer/Model	CCEC Cummins KTA19-G3
No.of Cylinders	6
Displacement	18.9L
Bore and Stroke	159*159(mm)
Compression ratio	13.9:1
Rated RPM	1800rpm
 Max.standby power at rated 1800RPM 	511KW
Aspiration	Turbocharged and aftercooled
Governor Type	GAC governor
 Exhaust Gas Flow @Standby Rating 	1713L/S
 Exhaust Temperature @Standby Rating 	491 ℃
 Intake Air Flow@Standby Rating 	647liter/s
Fuel System	Direct Injection Cummins PT
 100%(Prime Power) Load 	111Liter/H
 Lubrication System Min. capacity 	32L
 Total Coolant Capacity 	30L

Alternator Data

Manufacture/Type	Stamford/HCI544C	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

Control Panel



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

• Features: receive remote output signal from ATS and realize auto start and stop of generators.

• Auto Mains Failure controller, can realize further more can detect ATS and control directly.

•RS232 or 485 interface which can communicate with PC to realize remote operation.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Others

Engine	Alternator	Fuel System	Control System
Pre-heater	 Anti Condensation Heater Drop CT (For Paralleling) 	5	 Remote Control Panel Auto Transfer Switch (ATS) Paralleling System

Electricity Output Cabinet

<image>

Warranty





QSAND Sanq Power

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.







Data Sheet